











BEST IN CLASS HEARING

RA5001 RAPTOR headset offers Active Noise Reduction (ANR) communication intelligibility, and situational awareness.

The RAPTOR headset provides monaural or stereo communication, passive and active hearing protection, clear communication intelligibility and hear through situational awareness, incorporated in a lightweight, comfortable and extremely rugged design. It is ideal for use with next-generation commercial and military intercom systems within wheeled vehicles, shelters, and tactical operations centres. The chest mounted press-to-talk (PTT) unit reduces head borne weight and allows users to select between microphone, listen-only, and radio modes.





BENEFITS & EXTRAS

RA5001 RAPTOR Medium Noise Environment Headset



- Active Noise Reduction (ANR) SNR 23 dB, for safer longer missions
- High intelligibility communications in medium noise environments
- Profiled earshell and headstrap assembly, allows user to put on and take off whilst retaining ballistic protection
- Battery powered Hear Through (HT) microphones, for accurate situational awareness runs on AA battery
- High reliability in harsh and wet environments - IP67 immersible
- Chest mounted switchbox reduces on the head weight and physical burden
- Resistant to ferrous particles for continuous use in high iron environments
- Swappable boom microphone assembly to accommodate left or right handed shooters and reversible molle clip for left or right hand users



ACCESSORIES & ADD-ONS



EARCUSHION KIT 568989



MICROPHONE MUFFLER 568990



NECKBAND + OVERHEAD STRAPS



NECKSTRAP WITH BUCKLE

568992



HEADBAND COVER

701535

BATTERY COVER

568993



CHINSTRAP

553435



CHINSTRAP WITH BUCKLE

553436



EXTENSION CABLE

PART NUMBER UPON



SOFT LINER

566743/S-M 566743/M-L



HEADBAND ASSEMBLY

701549 CONVERSION KIT



BALLISTIC HELMET V50 RATING 650m/s

701140-X COLOURS AVAILABLE



BUMP HELMET (NON BALLISTIC)

701019-X COLOURS AVAILABLE



HEADSET/HELMET STORAGE BAG (PADDED)

701145



WEIGHT ON THE HEAD	499 g (17.6 ounces)				
NAPEBAND FORCE (ADJUSTABLE)	9.0/13.9 N (2.0/3.1 pounds)				
COMMUNICATION MODES	Mono and Stereo options				
FREQUENCY RESPONSE	250 Hz to 4.5 kHz				
INPUT IMPEDANCE	500Ω				
COMMS SENSITIVITY	Nominal 103 dB SPL				
BOOM MICROPHONE	150 Ω dynamic noise cancelling, antimagnetic, immersible				
MICROPHONE SENSITIVITY	Typical -56 dB				
ACTIVE NOISE REDUCTION (ANR)	ANR external powered				
PTT SWITCH	3 positions, located on switchbox				
HEAR THROUGH (HT) CONTROL	Off/On button on switchbox				
EXTERNAL POWER (HT + ANR)	13.5 to 33 VDC				
INTERNAL POWER (HT)	1 x AA 1.5 V cell, up to 150 hours				
INTERFACE CABLE	Terminated to suit requirements				
TEMPERATURE	-40° / +51°C Operating -57° / +71°C Storage				

IMMERSION	IP67, 1 meter for 2 hours
ELECTROMAGNETIC CONFORMITY	EN61000, MIL-STD-461F 50 V/m, EN55022, EN55024, ESD
SAFETY	EN60950-1
NOISE ATTENUATION	EN352, ANSI S3.19, ANSI S12.42
MTBF	32,714 hours
EXPORT CONTROL	Commercial product, No Licence Required
ENVIRONMENTAL TESTS	EN60068, MIL-STD-810G

Certified to: shock, bump, impact, vibration, dust, sand, humidity, mist, salt fog, driving rain, immersion, solar, altitude, fungal and fluid contamination.

Noise Reduction

FREQUENCY	HZ	125	250	500	1000	2000	4000	8000
MEAN	dB	23.6	19.1	13.8	24.6	29.7	38.7	37.3
STDEV	dB	1.3	1.2	1.8	0.6	0.6	0.3	0.4

 ${\tt SNR=23}\,,\ {\tt H=28}\,,\ {\tt M=19}\,,\ {\tt L=16}\,,\ {\tt NRR=18}$

PRODUCT PART NUMBERING SYSTEM

Part Number	Mono	Stereo	Microphone		Switching			C	NGN	Contour	Downlead length (mm)	
			Amplified	Switched	Lock	Centre	Momentary	Connector	NSN	System	Upper	Lower
RA5001/1/0025	√		√		470 Ohm	Off	0 Ohm	AP107	5965-99-615-7785	VIC3, Tocnet, RF7800i	465	370
RA5001/1/1026	1		V		470 Ohm	Off	0 Ohm	AP-107		VIC3, Tocnet, RF7800i	685	1000
RA5001/1/2020	V		V		Off	Off	0 Ohm	AP-107	5965-99-156-1884	SOTAS, DRS	465	370
RA5001/1/4024	V		√	√	Off	Off	0 Ohm	AP-107		FONET	465	370
RA5001/1/5042		V	V		470 Ohm	Off	0 Ohm	AP-107		SOTAS	465	370
RA5001/1/5052		1		V	22k Ohm	Off	0 Ohm	AP-107		Meshnet	465	370



IMTRADEX HÖR-SPRECHSYSTEME GesmbH

