



TECHNICAL DATA

Microphone:
 Directivity: Unidirectional
 Impedance: 1.0kΩ
 Sensitivity: -49±3dB (0dB=1V/Pa)
 Frequency Range: 100-16,000Hz
 Operating Temp: -20°C~+60°C
 Storage Temp: -25°C~+70°C

Speaker:
 Size: ø30 mm
 Input Power: 50 mW (1.26V)
 Max Power: 100 mW (1.79V)
 Impedance: 32Ω ±10% at 1kHz, 0.18V
 Sound Pressure: 122±3dB at 1kHz
 Resonance Frequency: 150±30 (20%) Hz
 Frequency Range: 20Hz ~ 20,000Hz
 Operating Temp: -25°C ~ +50°C
 Storage Temp: -25°C ~ +50°C



PLX COMPATIBLE QD



LEATHERETTE CUSHION



Order Code
Commander-PM

Order Code
Commander-PB

Commander

Professional office and contact centre headset.
 Fitted with 60mm leatherette ear cushions and padded T-bar, suitable for regular phone users.

Overview

Features	Single or dual speakers Left / right speaker side compatible Stereo audio sound for music and mono audio for speech Surround Shield™ noise cancelling microphone Fully flexible microphone for exact positioning 270° adjustable microphone boom 'Put and stay' ratchet microphone boom arm Swivel T-bar with padded leatherette cushion Overhead, sure-fit fully adjustable headband
What's included	Headset fitted with 60mm leatherette ear cushions and supplied with Quick Start Guide
Headset Weight	~ 62g / ~ 82g
Connection	PLX fitted as standard or GN** compatible QD options
Compatibility	For full range of bottom leads* and compatibility information - Go to Jpltele.com
Certifications	UKCA, CE, FCC, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 40
EAN:	Commander-PM: 5060126958758, Commander-PB: 5060126958772
SKU:	Commander-PM: 575-365-001, Commander-PB: 575-365-002

